

プラスチックリール ラインナップ

※帯電防止材もご用意ございます

JEITA規格リール

【N：ナチュラル C：導電 E：エコ】

| 中芯形状 | 外径 | 中芯 | 材料 | 巾 (mm) | | | | | | | | | | | | | | | |
|--------------------|------|------|----|--------|---|----|----|----|----|----|----|----|----|---|---|---|---|--|--|
| | | | | 4 | 8 | 12 | 16 | 24 | 32 | 44 | 56 | 72 | 88 | | | | | | |
| 真円 | φ178 | φ60 | C | ● | | | | | | | | | | | | | | | |
| | φ254 | φ80 | N | | | ● | ● | ● | | | | | | | | | | | |
| | | | C | | | ● | ● | ● | | | | | | | | | | | |
| | | φ100 | N | | | | ● | ● | | | | | | | | | | | |
| | | | C | | | ● | ● | ● | ● | ● | ● | | | | | | | | |
| | φ330 | φ80 | N | | ● | ● | ● | ● | ● | ● | ● | ● | | | | | | | |
| | | | C | | ● | ● | ● | ● | ● | ● | ● | ● | | | | | | | |
| | | | E | | ● | ● | ● | ● | ● | ● | ● | ● | | | | | | | |
| | | φ100 | N | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | | |
| | | | C | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | | | |
| | | | E | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | |
| | φ380 | φ80 | N | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | | |
| | | | C | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | | | |
| | | | E | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | |
| | | φ100 | N | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | |
| | | | C | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | | | |
| | | | E | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | |
| | φ150 | N | | | | | | ● | ● | ● | | | | | | | | | |
| | | C | | | | | | ● | ● | ● | | | | | | | | | |
| | | E | | | | | | ● | ● | ● | | | | | | | | | |
| φ380 ^{※1} | φ80 | N | | | ● | ● | ● | ● | ● | ● | ● | | | | | | | | |
| | | C | | | ● | ● | ● | ● | ● | ● | ● | | | | | | | | |
| | | E | | | ● | ● | ● | ● | ● | ● | ● | | | | | | | | |
| エスカルゴ | φ330 | φ100 | N | | | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | | | |
| | | φ150 | N | | | ● | ● | ● | ● | ● | ● | ● | | | | | | | |
| | φ380 | φ100 | N | | | ● | ● | ● | ● | ● | ● | ● | ● | ● | ● | | | | |
| | | φ150 | N | | | ● | ● | ● | ● | ● | ● | ● | | | | | | | |


※1 軽量化リール

カスタム品

【N：ナチュラル C：導電 PPE：耐熱】

| 品名 | 外径 | 中芯 | 巾 (mm) | 材料 |
|--------------|------|------|--------|---------|
| DR18-08HR | φ180 | φ60 | 8 | PPE |
| DR18-12HR | φ180 | φ60 | 12 | PPE |
| 100-50-9 | φ100 | φ50 | 9 | N |
| 120-60-4 | φ120 | φ60 | 4 | N (黒着色) |
| DRIII33-12HR | φ330 | φ100 | 12 | PPE |

※HRは耐熱仕様です



エコ材とは？

使用済みの成形されたリールを選別後、リベレットし成形し直したリールです。環境にも優しく、価格を抑えることが

記載している以外の製品も取り揃えております。お気軽にお問い合わせ下さい。